
. 5/02

DART AEROSPACE LTD	Work Order:	22150
Description: Label	Part Number:	D3309-3
Dwg: D3309 Rev. A	Qty:	10
		Page 1 of 1

Step	Location	Procedure	Ву	Date	Qty
1	DC	Issue Traveler	*	05.02.07	10
2	PG	Issue P/O: 7004510 Make as per Dwg D3309 Black letters (0.15" min. height) on white adhesive back Possible Manufacture: From 3M 7 mil masking film # 8522CP or Avery IPM # 2031 Possible Supplier: Studio Lettrage	14	05.02.07	10
3	RG	Material release note is required Receive and Inspect for transit damage Enure material release note is attached	1.0	05/02/11	10
4	QC6	Inspect dimensions as per Dwg D3309	U	08-02-05	60
5	ST	Identify and Stock	CL	25/02/15	10
6	AC	Cost / part 12.79	540	05-02.16	10
7	DC	Close W/O // . oc Inspect Level 21	\$	05.02.16	10

Rev	Date	Change	Revised By	Approved
Α	04.12.13	New issue	KJ/RF	*



Dart Aerospace Ltd


W/O:		WORK ORDER CHA	WORK ORDER CHANGES									
DATE	STEP	PROCEDURE CHANGE	Ву	Date	Qty	Approval Mfg / Design Mgr	Approval QC Inspector					
L												
NCR:		WORK ORDER NON-CONFO	RMANCE (NC	R)								
	1					r	Т					


NCR:	WORK ORDER NON-CONFORMANCE (NCR)							
		Description of NC		Corrective Action Section B		Verification	Approval	Approval
DATE	STEP	Section A	Initial Design Mgr	Action Description Design Mgr	Sign & Date	Section C	Design Mgr	QC Inspector
		·		·				

Part No:	PAR #:	Fault Category:	NCR:	Yes	No	DQA:	Date:
NOTE: Date & initial all entries				QA: N	I/C C	osed:	Date:



DESIG	13	DRAWN BY	DART AEROSPACE LTD HAWKESBURY, ONTARIO, CANADA	
CHECK	KED	APPROVED	DRAWING NO. F	REV. A
-	RE		D3309 SHEET 1	OF 1
DATE			TITLE	SCALE
04.1	2.09		LABEL	1:1
Α		04.12.09	NEW ISSUE	





SHOP COPY

RETURN TO **ENCINCERING**

UNGENTRE LED COPY

SUDUE TO THE ENDMENT VILLEOUT NOTICE

WORK ORDER NO. 22150

NOTES:

1) MATERIAL: BLACK LETTERS (0.15" MIN HEIGHT) ON ADHESIVE BACK MANUFACTURED FROM 3M 7 MIL MASKING FILM #8522CP OR AVERY IPM #2031

Copyright © 2004 by DART AEROSPACE LTD

THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT IS NOT TO BE USED FOR ANY PURPOSE OR COPIED OR COMMUNICATED TO ANY OTHER PERSON WITHOUT WRITTEN PERMISSION FROM DART AEROSPACE LTD.

Job Costing Report

Dart Aerospace Ltd.	_	•	Feb 02, 2005
Hawkesbury			02:44 pm

	, .
Department Code	•
Burden Flags	: NNNNNNN
WO Status	: Open
Invoice State	: Not Invoiced
Invoice Date	: .
Invoice Number	•
Invoice Amount	: 0.00
Order Entry No	•
OE Value	: 0.00
Est Margin	: 0.000%
Actual Margin	: 0.000%
	Burden Flags WO Status Invoice State Invoice Date Invoice Number Invoice Amount Order Entry No OE Value Est Margin

Ok for Approval :
Approval Rec'd : \$0 Posted to Finished Goods

		Estimated	Actual	Var. %	Posted	To Post
Material Cost	:	0.00	57.05	100.00	0.00	57.05
Engineering Hours	:	0.00	0.00	0.00		
Engineering Cost	:	0.00	0.00	0.00	0.00	0.00
Production Hours	:	0.00	0.00	0.00		
Production Cost	:	0.00	0.00	0.00	0.00	0.00
Packaging Hours	:	0.00	0.00	0.00		
Packaging Cost	:	0.00	0.00	0.00	0.00	0.00
OverHead Hours	:	0.00	0.00	0.00		
OverHead Cost	:	0.00	0.00	0.00	0.00	0.00
CNC Hours	:	0.00	0.00	0.00		
CNC	:	0.00	0.00	0.00	0.00	0.00
Misc. Hours	:	0.00	0.00	0.00		
Misc.	:	0.00	0.00	0.00	0.00	0.00
		=======	========			
Burden	:	0.00	0.00	0.00		
		========	========	======		
Total Cost	:	0.00	57.05	100.00		
Margin	:	0.000	0.000			
Selling Cost	:	0.00	57.05			

		Estimated		Actual
Labour Hrs/Amount Done	:	0.00		0.00
Profits/(Loss)	:	0.00	(-57.05)

Product Bulletin 8522



Release F, Effective January 2003 Black bar in margin indicates a change

Scotchcal [™] Opaque Imaging Media 8522

Description

This media is specially formulated to dry quickly after printing. Production of outdoor weatherable and long-term indoor durable graphics is now easier than ever. Its changeable adhesive allows easy removal for up to one year.

Advantages

- Optimized for use with selected Epson Stylus Proprinters and Epson Archival inks.
- Optimized for use with selected HP DesignJet Printers and HP DesignJet Ink System UV or HP83UV Color Ink System
- For making opaque, laminated graphics that are outdoor weatherable and long-term indoor durable
- Media:
 - For opaque (reflective) graphics
 - Changeable, easy to remove from warranted substrates up to 1 year later
 - Dries quickly after printing so the overlaminate can be applied almost immediately
 - Low slippage paper liner for superior tiling
- Overlaminates:
 - Provide additional UV (ultraviolet) and physical protection for making weatherable finished graphics
 - Available in luster and matte gloss
 - Adhesive allows for heat-assisted or cold-temperature lamination

Applications and Uses

3M ™ Scotchcal ™ Changeable Opaque Imaging Media 8522 is intended only for ink jet printing and for use with the listed Compatible Products and Equipment and the following applications. Any other application is NOT warranted by 3M or covered by the worldwide 3M ™ MCS ™ Warranty unless 3M gives its prior written approval for the application.

- First surface images (the image is on top of the film) for opaque posters and signs, including:
 - Graphics for vans, personal vehicles, trucks and buses
 - Novelty posters
 - Retail and point-of-purchase displays
 - Information graphics such as maps and directories
 - Entertainment promotions in museums, zoos, parks, theatres, sports venues
 - Education and presentation graphics

- Legal and courtroom exhibits
- For flat or simple curved surfaces, with or without rivets, used in vertical (± 10°) applications

Limitations of End Uses

The following uses and applications are specifically NOT

- Fleet applications in areas that use salt for winter road maintenance
- Application to non-warranted substrates, including wallboard
- Applications subjected to gasoline vapors or spills
- Application to corrugated or highly irregular surfaces or sharply raised areas
- Graphics applied to stainless steel, including stainless steel vehicles
- On flat surfaces with rivets, tenting of 4 to 10 mm around rivets may be expected; rivets may be cut around to eliminate tenting.

Note: Standard ink jet technology is water based. Waterbased chemistry is susceptible to the extremes of heat and humidity. This is a factor in most product constructions on the market. Read the Fabrication, Shelf Life and Storage sections in this bulletin. Staying in the middle of these ranges always provides optimum performance.

Compatible Products and Equipment

Thermal Ink Jet Printing Systems

- Epson Stylus Pro 9500, Stylus Pro 10000 printer
 - Epson Archival Inks
- Epson Stylus Pro 10600 printer
 - Epson Archival Inks
- HP DesignJet Printers 2000 and 3000 series
 - HP DesignJet Ink System UV (pigment-based ink)
- HP DesignJet Printers 5000 series
 - HP83UV Color Ink System

Overlaminates (required)

- 3M [™] Luster Overlaminate 8519 (semi-gloss)
- 3M[™] Matte Overlaminate 8520

Note: For the full product names of the 3M products listed on this page, please see page 1.

Warranted Substrates

Media 8522 is warranted for use on the following rigid substrates.

Some substrates may "out-gas", resulting in tiny bubbles throughout the surface of the graphic. For maximum performance, be sure the substrate you select is properly cleaned and prepared as recommended by the manufacturer. See Instruction Bulletin 5.1 for additional information.

- Alodine (anodized aluminum)
- Automotive panels (automotive painted steel)
- Fruehauf (painted aluminum)
- FRP (fiberglass reinforced plywood)
- Glass
- Imron® (polyurethane-painted metal panel)
- Acrylic
- Sintra[™] board

Test and Approve Non-warranted Substrates Before Use

Media 8522 is not warranted for any substrate other than those listed above. If you want to use it for other substrates, 3M recommends that you test and approve the media for both adhesion and removal characteristics.

Characteristics

Characteristic	Description
Media	7 mil, white, opaque graphic film
Liner	Low-slippage, lay flat paper
Adhesive	Changeable, pressure sensitive
Thickness (media and adhesive)	7.5 to 8 mil (nominal)
Application substrates	See Warranted Substrates, above
Application surfaces	Flat or simple curved surfaces, with or without rivets, used in vertical (± 10°) applications (no corrugations)
Application temperature range	28° to 110°F (-2° to 43°C) (air and surface)
Roll sizes	36" x 45 feet (914 mm x 13.5 m) 54" x 45 feet (1372 mm x 13.5 m)

How to Become a 3M Ink Jet Registered Fabricator

Only 3M Thermal Ink Jet Registered Fabricators are eligible to offer 3M MCS warranted graphics. In order to become certified, a fabricator must complete the requirements as specified in the 3M Ink Jet Graphics Registered Fabricator Reference Manual located on the 3M website at www. scotchprint.com

Effective Performance Life

To obtain the warranty given below, the graphics must be made according to 3M's recommendations which are detailed in the Warranty and Limited Remedies on page 3. Also see the section, Removability.

Warranted Durability

Media 8522 with	Epson Printers		HP Printers	
Overlaminate 8519 or 8520	Outdoor	Indoor	Outdoor	Indoor
Applied to Warranted Substrates	2 years	5 years	3 years	5 years

Removability

Imaging media 8522 is removable from warranted substrates for 1 year without the aid of chemical strippers or accessories. Refer to Instruction Bulletin 4.23 for additional information.

Fabrication

Graphics must be made according to 3M's recommendations which are detailed in the Warranty and Limited Remedies on page 3.

See Instruction Bulletin 4.23 for detailed fabrication, printing and mounting information.

Graphic Construction Options

Opaque (Reflective) Graphics

Opaque graphics made with imaging media 8522 require an overlaminate and an opaque substrate.

Viewer/Light Source	
	Overlaminate 8519, 8520 Adhesive on bottom
	Imaging Media 8522 Image on top; adhesive on bottom
	Opaque Substrate

Note: For the full product names of the 3M products listed on this page, please see page 1.

Shelf Life and Storage

- 3M[™] Scotchcal [™] Changeable Opaque Imaging Media 8522 has a shelf life of one year.
- Storage conditions (new and partially used rolls). For optimum performance, use the middle of these ranges:
 - Original packaging, including plastic wrap
 - Relative humidity of 20% to 80%
 - Temperature of 33° to 104°F (0° to 40°C)
 - Away from direct sunlight
- Do not stack unprotected rolls or lay sharp or heavy objects on them.

Health and Safety

When handling any chemical products, read the manufacturers' container labels and the Material Safety Data Sheets (MSDS) for important health, safety and environmental information.

To obtain MSDS sheets for 3M products:

- By fax, call 1-800-364-0768 in the US and Canada or 1-650-556-8417 for all other locations.
- Electronically, visit us at http://www.3M.com/msds.
- By mail, or in case of an emergency, call 1-800-364-3577 or 1-651-737-6501.

When using any equipment, always follow the manufacturers' instructions for safe operation.

Warranty and Limited Remedies

3M ™ MCS ™ Warranty for Graphics Produced on HP DesignJet Printers and Epson Stylus Pro Printers

The following is made in lieu of all other express or implied warranties, including any implied warranty of merchantability or fitness for a particular purpose: We warrant graphics produced by a 3M lnk Jet Registered Fabricator made with imaging media 8522, printed on an approved HP thermal ink jet printer according to HP's recommendations or Epson Stylus Pro printer according to Epson's recommendations, overlaminated with 8519 or 8520, and applied to a Warranted Substrate according to 3M's recommendations. These

graphics are covered against failure caused by ultraviolet light, temperature extremes, pollution, and other elements.

If a graphic fails to perform in accordance with 3M product specifications within this time frame, 3M will replace the materials at no charge. These remedies are exclusive. In no case shall 3M be liable for any direct, indirect, or consequential damages, including any labor charges.

3M Related Literature

Listed below is related 3M technical literature that may be of interest. You may view and print these Bulletins from our Web site at www.scotchprint.com, or order them via our Faxon-Demand (FOD) system. Call one of these phone numbers to order the desired bulletins, and specify the FOD document number provided in the chart.

United States or Canada: 1-800-364-0768 International: 1-651-732-6506

Subject	Bulletin No.	FOD No.		
Product Bulletins				
3M [™] Scotchcal [™] Overlaminate 8519 and 8520	8519/8520	4524		
Instruction Bulletins				
Making thermal ink jet graphics	4.23	6523		
Application, substrate selection, preparation and substrate-specific application techniques	5.1	7001		
Warranties				
Worldwide 3M To MCS To Warranty Packet (includes all Commercial Graphics MCS Warranties)				
Worldwide 3M™ MCS™ Warranty Overview-Folder				

3M, Scotchcal and MCS are trademarks of 3M.
Epson and Stylus Pro are trademarks of Epson.
HP and DesignJet are tradenames of Hewlett Packard.
Sintra is a trademark of Swiss Aluminum Ltd.
Imron is a registered trademark of DuPont in the United States

Bulletin Change Summary

The Epson Stylus Pro Printers 9500, 10000 10600, and Epson Archival Inks have been added to this bulletin. Additional changes resulting from this addition are marked with black bars in the margin.

3W

Commercial Graphics Division 3M Center, Building 220-6W-06 PO Box 33220 St. Paul, MN 55133-3220 USA General Info. 1-800-374-6772 Technical Info. 1-800-328-3908 Fax 1-651-736-4233

3M Canada P.O. Box 5757 London, Ontario Canada N6A 4T1 1-800-265-1840 Fax 519-452-6245

Fax-on-Demand 1-800-364-0768 US/Canada or 1-651-732-6506 International Fax-on-Demand document: 4506 www.scorchorint.com

3M México, S.A. de C.V.

Av. Santa Fe No. 55 Col. Santa Fe, Del. Alvaro Obregón México, D.F. 01210 52-55-52-70-04-00 Fax 52-55-52-70-22-77 3M Puerto Rico, Inc. Puerto Rico Industrial Park P.O. Box 100 Carolina, PR 00986-0100 787-620-3000

787-620-3000 Fax 787-750-3035

©3M 2003. All rights reserved.

Product Bulletin 8522 – 3